

Daniel Krutiš**Od:** Martin Sgalitzer [martin.sgalitzer@blizzard.cz]**Odesláno:** 31. března 2010 18:27**Komu:** 'Lukáš Černý'**Kopie:** 'Daniel Krutiš'**Předmět:** Zheijang SOPRAY Solar - 180W mono**Mono 175W**

1580x808x35mm

Specification	Wp(W)	Vmp(V)	Imp(A)	Voc(V)	Isc(A)	L*W*H(mm)	Glass(mm)	Cell(mm)	Weight(Kg)
SR-150	150	34.4	4.37	43.0	4.86	1580x808x35	1574x802	125x125	14.5
SR-160	160	34.4	4.66	43.0	5.00	1580x808x35	1574x802	125x125	14.5
SR-165	165	35.87	4.60	43.0	4.90	1580x808x35	1574x802	125x125	14.5
SR-170	170	36.1	4.71	43.3	5.00	1580x808x35	1574x802	125x125	14.5
SR-175	175	36.45	4.81	43.7	5.10	1580x808x35	1574x802	125x125	14.5
SR-180	180	36.73	4.91	44.3	5.20	1580x808x35	1574x802	125x125	14.5

short-circuit current	TK(1)	-0.47%/°C
temperature coefficients of im	+0.04%/°C	-0.38%/°C
temperature coefficients of vm	-0.38%/°C	+0.10%/°C
Limits		
MAX SYSTEM VOLTAGE	1000Voc	
OPENING MODULE TEMPERATURE	-40..... -90°C	
MAX LOAD		